



## H716a4

<b>Cabinet Color</b>	Black
<b>Panel</b>	TFT Active Matrix LCD, Slim Cabinet VIS: 17" ( 43.2cm ), Diagonal Hard Coating (3H), Anti-glare Treatment
<b>Pixel Pitch</b>	0.264mm x 0.264mm
<b>Display Area</b>	338mm x 270mm
<b>Brightness</b>	300 cd/m2 (typ)
<b>Contrast Ratio</b>	700:1 (typ)
<b>Response Time</b>	5ms (typ)
<b>Viewing Angle</b>	Horizontal: 140 Degrees Vertical: 135 Degrees
<b>Compatibility</b>	VESA, SXGA, XGA, SVGA, VGA Mac® Equipped With VGA Port
<b>Scanning Frequency</b>	Horizontal: 30K~80KHz Vertical: 55~75 Hz
<b>Pixel Frequency</b>	135MHz
<b>Maximum Resolution</b>	1280x1024@75Hz
<b>Recommended Resolution</b>	1280x1024@60Hz
<b>Resolutions Supported</b>	720x400@70Hz, 640x480@60/72/75Hz, 800x600@56/60/72/75Hz, 832x624@75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
<b>Color</b>	16.2M
<b>Signal Input</b>	Video: 0.7Vp-p, RGB Analog Separate Sync: TTL Level H/V Sync: Positive / Negative
<b>Connectors</b>	RGB Signal: 15-pin D-sub (3-Pin Plug CEE22)
<b>Power Source</b>	Universal 100~240VAC, 50/60Hz (Internal Power Supply)
<b>Power Consumption</b>	36 Watts (Max.)
<b>Plug &amp; Play</b>	DDC2B
<b>EPA ENERGY STAR®</b>	Yes
<b>User Control</b>	Menu, Left, Power, Right, OK/Auto
<b>OSD Function</b>	Contrast, Brightness, Color Temperature, H/V Position, Volume, Auto Configuration, Advanced (Language, Clock, Phase, Reset, OSD Position, OSD Timeout)
<b>OSD Languages</b>	English, French & Spanish
<b>Regulations</b>	cULus, FCC, CE, Works with Windows Vista, ROHS
<b>Other Features</b>	VESA 100mm Wall Mount Compliant*, Kensington Security Slot
<b>Built-in Speakers</b>	1W x 2
<b>Dimensions (WxHxD mm)</b>	Monitor: 374x375x177; Carton 424x432x145
<b>Dimensions (WxHxD inches)</b>	Monitor: 14.7x14.8x7.0; Carton: 16.7x17.0x5.7
<b>Weight</b>	8.05 lbs (3.66kgs) Net 10.45 lbs (4.75kgs) Gross
<b>Loading Qty w/pallet</b>	20' = 832 pcs.; 40' Std = 1728 pcs.
<b>UPC Code</b>	685417103584